

Product Data Sheet

No. 51215 - 01/10

MAX BURTON® BUTANE FUEL CARTRIDGE

AEROSOL VOC <100%

PRODUCT NUMBER: 1215 7.8 oz. net wt.



I. GENERAL DESCRIPTION

Features: Max Burton® Butane Fuel Cartridge contains a highly refined and filtered liquefied petroleum gas (LPG) that is designed to be used in a variety of portable gas appliances. It features a notched collar valve to ensure proper alignment with gas appliance and a rim vent release dome that allows gas to release safely in the event of overpressure. The can is disposable (cannot be refilled) and UL approved.

Benefits: Max Burton Butane Fuel is purified for excellent flame quality. The can is specifically designed to fit all Max Burton table top burners and lanterns.

Uses: Use along with any Max Burton appliance while camping, picnicing, tableside cooking, or catering. Great addition to any emergency preparedness kit.

Warnings: Refer to product operating instruction guides for use in the appropriate appliance. Extremely Flammable. DO NOT use or store near heat or open flame. DO NOT puncture or incinerate. Use in well ventilated area. DO NOT attempt to light appliance when gas odor is detected. Keep out of the reach of children. Once all of the fuel is used, discard empty can in accordance with local aerosol disposal regulations. Refer to the Material Safety Data Sheet for specific information on material hazards.

This product contains and when burned produces chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Designed for use in Max Burton portable gas appliances such as table top burners, lanterns or other UL listed appliances. Failure to use in the above appliances may result in unsafe operation and danger to the operator.

Compatible with:

Industrial Torch Head #1252
Mr. Max Table Top Burner #8254

Packaging:

Each can (211x604):	7.8 oz. net wt. (220 g)	13.1 fl. oz. (388 ml)
Case (12/case):	11 lbs. (4.9 kg)	0.56 CF (0.016 CM)



AerVOE Industries, Inc.
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service
www.aerVOE.com • www.athenabrands.com • www.zynolyte.com

II. CHARACTERISTICS AND PROPERTIES

Specifications:

None

Appearance:

Clear gas, non-staining

Color:

Translucent

Odor:

Odorized gas

Performance and Chemical Properties:

Aerosol

Weight per gallon 4.83 lbs
Specific gravity (H₂O = 1) 0.58 @ -50°C
Flammability: Label marking Extremely flammable
Flash point..... <0°C
Volatile Organic Compound level 100%
Operating temperature range 40° to 110°F (5° to 43° C)
Auto ignition temperature range 761° to 842°F (405° to 450°C)
Boiling point..... -40° to 30°F (-40° to 1°C)
Vapor pressure 30 psi @ 70°F

Base Materials LPG Hydrocarbon Propellant

III. SHIPPING, STORAGE AND HEALTH

IMDG number UN1965
D.O.T. container spec..... 2P - DOTREG.M4981
D.O.T. shipping description Butane
Warehouse storage level number NFPA 30B Level 3
Hazardous class (CFR-49) 2.1
Storage temperature 32° to 120°F (0° to 49°C)
HMIS ratings
Health..... 1
Fire 4
Reactivity..... 0

IV. MISCELLANEOUS

Does not contain ozone depleting substances.

V. WARRANTY

The statements made herein, on labels, product bulletins or by any of our employees or agents concerning this material are given for information only. Any liability whatsoever of Athena Brands. to the user of the product, is limited to replacement of the product or purchase price refunded.